

RAMPART

Electromechanical actuator for sectional doors 24 Vdc





RAMPART Technical features

M COMUNELLO






TECHNICAL CHARACTERISTICS

TEOTIMONE OF IMMENOTERIOTION		
	RAMPART 600 24V	RAMPART 1000 24V
Power	230V (±10%) / 50Hz	230V (±10%) / 50Hz
Maximum pulling effort (force needed to start door move)	600 N	1000 N
Nominal pulling effort (force needed to maintain door move)	200 N	300 N
Maximum door leaf weight	110 kg	210 kg
Maximum opening speed	0,14 meters/seconds	0,14 meters/seconds
Maximum continuous motortime	60 seconds (intermittent operation mode)	60 seconds (intermittent operation mode)
Current consumption	110 W	150 W
Remote controls	433,92MHz / dynamic code 200 Remote controls max	433,92MHz / dynamic code 200 Remote controls max
Insulation class	II	II
Protection rating (IP)	IP20	IP20
Temperature range	-20°C/+50°C	-20°C/+50°C
Actuator weight	4,5kg	5,0kg

DIMENSIONS (mm)



COLOURS AVAILABLE: WHITE, BLACK





COMUNELLO® Copyright 2020 - All rights reserved 3 2 COMUNELLO® Copyright 2020 - All rights reserved

OFFICIAL DEALER:



AUTOMATION FOR GATES, DOORS AND BARRIERS

FRATELLI COMUNELLO S.P.A.

HEADQUARTERS

Via Zarpellon, 33
36027 San Giuseppe di Cassola, Vicenza, Italy
Tel. +39 0424 585111 Fax +39 0424 533417
info@comunello.it www.comunello.com

REGISTERED OFFICE

Via Cassola,64 - C.P.79
36027 Rosà, Vicenza, Italy
Tel. +39 0424 585111 Fax +39 0424 533417
info@comunello.it www.comunello.com